

EDGE™ Housing

2 rack units, holds up to 24 EDGE modules or panels

CORNING

EDGE™ HD solutions are high-density preterminated optical cabling solutions offering industry-leading connector density. With unprecedented finger access, there is no need for additional tools enabling faster moves, adds and changes (MACs).

Features and Benefits

Universal wired components

Enable moves, adds and changes without polarity concerns; provide a simple migration path between 2-fibre and parallel optic applications

Sliding drawers

Allow unprecedented finger access, easier jumper/harness routing and port identification

Integrated strain-relief plate can rotate 90°

Allows for rear cable entry direction, as well as the traditional side cable entry

Removable top covers on the 1 U and 2 U housings

Provide easier access to modules and panels



Part Number: EDGE-02U



Part Number: EDGE-02U

EDGE™ Housing

2 rack units, holds up to 24 EDGE modules or panels

CORNING

Specifications

General Specifications	
Application	Data Centre, Data Centre LAN/SAN, Enterprise Networks
Product type	Fibre Optic Hardware
Mounting type	Rack Mount, Cabinet-mount
Mounting Technology	Adjustable depth settings
Access type	Front and rear access slidable
Lockable	Yes, rear side

Design - Hardware	
Housing type	EDGE™ HD
Height Unit	2U
Number of Panels per Housing	24
Housing Colour	Silver
Fibre Capacity	288
Cable Entry Direction	Rear
Cable entry type	Side brush entry
Colour	Silver
Number of modules	24

Mechanical Characteristics	
Dimensions (W x D x H)	432 mm x 561 mm x 88 mm (17 in x 22.1 in x 3.5 in)
Weight	8.6 kg (19 lb)
Minimum Cabinet Size	800 mm

Chemical Characteristics	
RoHS	Free of hazardous substances according to RoHS 2002/95/EG

EDGE™ Housing

2 rack units, holds up to 24 EDGE modules or panels



Ordering Information

Part Number	EDGE-02U
Product Description	EDGE™ Housing, 2 rack units, holds up to 24 EDGE modules or panels
EAN Code	4056418144498
Module Capacity	24
Trunk Capacity	24 (size 1 or 2, double stack cradle)

Shipping Information

Units Per Delivery	1/1
Packaging Dimensions (W x D x H)	565 mm x 660 mm x 216 mm (22.3 in x 27.4 in x 8.4 in)
Shipping Weight	10.9 kg (24 lb)



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY
00 800 2676 4641 · FAX: +49 30 5303 2335 · www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2016 Corning Optical Communications. All rights reserved.